



1m 3618

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT(S) : Treadwell, et al.  
TITLE : **MOTORIZED TOWING DEVICE**  
APPLICATION NO. : 10/577,384  
FILED : April 27, 2006  
CONFIRMATION NO. : 5053  
EXAMINER : Unknown  
ART UNIT : 3618  
LAST OFFICE ACTION : None  
ATTORNEY DOCKET NO. : PERY 2 00010

**TRANSMITTAL LETTER OF 35 U.S.C. § 119**  
**FOREIGN PRIORITY DOCUMENT**

Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

Dear Sir:

Applicants hereby claim priority under 35 U.S.C. § 119 for the above-identified U.S. utility patent application. This claim of priority is based upon:

Patent Application No. 2,447,019; filed October 27, 2003 in  
Canada.

As required by paragraph 2 of 35 U.S.C. § 119, enclosed herewith is a certified copy of:

Patent Application No. 2,447,019; filed October 27, 2003 in Canada.

**REMARKS**

It is respectfully submitted that the subject application is now complete and in better condition for examination.

Respectfully submitted,

FAY SHARPE LLP

26 MAR 07  
Date

Michael E. Hudzinski  
Michael E. Hudzinski, Reg. No. 34,185  
1100 Superior Avenue  
Seventh Floor  
Cleveland, OH 44114-2579  
216-861-5582

CERTIFICATE OF MAILING OR TRANSMISSION	
I hereby certify that this correspondence (and any item referred to herein as being attached or enclosed) is (are) being	
<input checked="checked" type="checkbox"/>	deposited with the United States Postal Service as First Class Mail, addressed to Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date indicated below.
<input type="checkbox"/>	transmitted to the USPTO by facsimile in accordance with 37 CFR 1.18 on the date indicated below.
	Signature: <u>Barbara Brazier</u>
Date: March <u>26</u> , 2007	Name: Barbara Brazier

N:\PERY\200010\bjb0005824V001.docx



**Office de la propriété  
intellectuelle  
du Canada**

Un organisme  
d'Industrie Canada

**Canadian  
Intellectual Property  
Office**

An Agency of  
Industry Canada


*Bureau canadien  
des brevets  
Certification*

*Canadian Patent  
Office  
Certification*

La présente atteste que les documents  
ci-joints, dont la liste figure ci-dessous,  
sont des copies authentiques des docu-  
ments déposés au Bureau des brevets.

This is to certify that the documents  
attached hereto and identified below are  
true copies of the documents on file in  
the Patent Office.

Specification and Drawings, as originally filed, with Application for Patent Serial No:  
**CA 2447019**, on October 27, 2003, by **SIMON TREADWELL** and  
**ALISTAIR JENKINS**, for "Motorized Towing Apparatus".

  
Agent certificateur/Certifying Officer

March 6, 2007

Date

**Canada**

(CIPO 68)  
31-03-04

OPIC  CIPO

5

Abstract

A new motorized tow-motor module with electronic control and a quick-release attachment mechanism is described to provide on demand motive power to a range of detachable containers or trolleys allowing heavy loads to be carried and moved between locations easily. The tow-motor includes a pair of load bearing wheels each attached to an axle supported inside a tubular monocoque chassis. In one embodiment of the invention the tubular monocoque chassis contains a pair of electronically controlled, variable speed, reversible, direct current motors connected to the axle(s) via a gear train and clutch assembly a rechargeable battery module and an electronic module for controlling the power applied to each of the electric motors in response to displacement and steering commands applied by the operator to a remote handle mounted controller.

5 Title Motorized Towing DeviceField of the Invention

10 The present invention generally relates to a new motorized tow-motor with electronic control and a quick release mechanism to provide when required assistive motive force and steering to a range of detachable accessory containers or trolleys allowing heavy loads to be transported and moved between locations easily. The present invention when connected via the proposed quick release mechanism to the wide variety of accessory containers and trolleys that will be familiar to those versed in the art has application to the movement of  
15 personal, business, industrial and garden items. The invention also has particular application to the provision of assistive motive power to those individuals who due to age injury or preference require assistance during the movement of heavy items over short to medium distances both outside or inside.

20 Description of Prior Art

The use of motor driven shopping carts, golf carts, and delivery trolleys or carts for the delivery or distribution of large quantities of goods to one or more locations are known and consist basically of familiar, expected and obvious structural configurations. Not  
25 withstanding the myriad of designs encompassed by the crowded prior art which have been developed for the fulfillment of countless objectives and requirements.

Known prior art shopping carts include U. S. Pat. No. 4,096,920 to Heyn; U.S. Pat. No. 4,771,840 to Keller; U.S. Patent No. Des. 309,517 to Hawkins; U.S. Pat. No. 4,020,916 to  
30 Noble; U.S. Pat. No. 4,750,578 to Brandenfels; and U.S. Pat. No. 5,064,012 to Losego.

Similarly U.S. Pat. No. 2,918,133 by Ericsson teaches a powered barrow or cart adapted for the handling and transportation of diverse materials. U.S. Pat. No. 3,266,813 to Bosko et al. discloses a mobile garden and refuse cart for safe, sanitary storage and sanitary cleanup or

5 pickup service. U.S. Pat. No. 3,485,314 to Herr teaches an article carrying land vehicle with a cargo container and with an optional stowable riding attachment. U.S. Pat. No. 3,791,470 by Baddorf et al. discloses a motorized wheelbarrow. U.S. Pat. No. 4,137,984 to Jennings et al. provides an automatic, self guiding transporter having electrically driven wheels activated by a control mechanism which senses the magnetic field around a buried guide  
10 wire. U.S. Pat. No. 4,203,609 by Mitchell et al. teaches a transport cart of the type used in industrial-commercial applications for movement of articles, preferably those loaded on pallets.

None of the foregoing prior art teaches or suggest the particular concept of a single  
15 electronically controlled tow motor with quick release mechanisms, to allow for the attachment of various accessory containers and trolleys to provide assistive motive power for the transporting of items as conceived by this invention. In this regard the tow motor device described substantially departs from the conventional concepts and designs of the prior art, and in so doing provides an apparatus that provides assistive motive power to the  
20 user allowing a wide range of items to be transported indoors and outdoors over a wide range of terrain with reduced physical effort.

It is an object of the present invention to provide a new motorized tow motor with  
25 electronic controls and quick release attachments which has many of the advantages of the motorised carts and delivery devices mentioned heretofore and many novel features that result in a new motor module which is not anticipated, rendered obvious, suggested, or even implied by any of the prior art, either alone or in any combination thereof.

30 It is another object of the present invention to provide a new electrically powered tow-motor which may be easily and efficiently manufactured and marketed.

5

It is a further object of the present invention to provide a new powered tow-motor which is of a durable and reliable construction.

10

An even further object of the present invention is to provide an electrically powered tow-motor which is susceptible of a low cost of manufacture with regard to both materials and labour, allow it to be sold at a price to the consuming public making such electrically powered tow-motor economically available to the buying public.

15

Still yet another object of the present invention is to provide an electrically powered tow-motor which provides in the apparatuses and methods of the prior art some of the advantages thereof, while simultaneously overcoming some of the disadvantages normally associated therewith.

20

Still another object of the present invention is to provide a new electrically powered tow-motor that may be quickly attached to a wide variety of load carrying containers and platforms increasing the device's utility and adaptability to many tasks .

25

Still another object of the present invention is to provide a new electrically powered tow-motor that by using electronic sensors and control circuitry is able to provide assistive motive force only when the addition of such assistance is required by the user to overcome increased loading or rolling friction thereby reducing average power consumption allowing greater periods of operation between recharging.

30

For a better understanding of the invention, its operating advantages and the specific objects attained by its uses, reference should be made to the accompanying drawings and descriptive matter in which there are illustrated preferred embodiments of the invention.

5 **BRIEF DESCRIPTION OF THE DRAWINGS**

The invention will be better understood and objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:

10

FIG 1a. base motor tow module without handle and control

FIG. 1b is a perspective view of the electrically powered tow-motor with a handle and control unit

15

FIG. 2 is a side elevation view of the present invention.

FIG. 3 is a front elevation view of the present invention.

20 FIG. 4 exploded view of the invention

FIG. 5 detail view of the handle

FIG. 6a Tow motor with typical accessory bearing quick connect disconnect system

25

FIG 6b Tow motor with another typical accessory bearing a quick connect disconnect system

FIG. 6c lower yoke arms rotated around tow motor yoke seat

30

FIG. 6d lower yoke arm latches hooked on upper yoke

FIG 6e latches locked in place by depressing locking arms



## 5 DESCRIPTION OF THE PREFERRED EMBODIMENT

The general purpose of the present invention which will be described subsequently in greater detail is to provide electric motive power to a range of containers; dolly's and trolleys by way of a modular tow motor with electronic control that attaches to, and  
10 provides assistive motive power to a wide variety of such accessories via a quick release and attachment mechanism and that is controlled by a force actuated steering and control module remotely attached to the load carrying container or trolley.

To allow this the present invention includes a pair of load carrying wheels each attached to  
15 an axle mounted and supported by a tubular monocoock chassis between the wheels and of a size smaller than the diameter of the wheels. In one embodiment the tubular monocoock chassis and accessible by removable access panels are a pair of reversible, variable speed, independently controllable load actuated direct current electric motors. The motors located within the tubular monocoock chassis may be connected to the drive axle of the wheels via a  
20 variety of gear drives and clutch mechanisms suitable for such purposes and optimised for the application. Preferably electrical energy required to provide the assistive motive power to the wheels is provided by a rechargeable battery pack also enclosed within the tubular monocoock chassis or directly mounted to it. To provide for varying levels of assistive power the motors are typically controlled by an electronic module containing field effect  
25 transistors or other similar devices that distribute electrical power to the motors in response to the magnitude of the force applied by the operator to the steering column.

The chassis housing preferably incorporates a quick connect/disconnect system that allow the unit to be coupled to a variety of accessories such as but not limited to containers or  
30 platforms that perform load carrying or towing for goods, personal items or other loads that must be transported from one location to another by the user of the device. One such version of the quick connect/disconnect system is shown in the attached drawings. This system typically is comprised of a upper stationary yoke, a lower rotating yoke clamp, and a buckle type closure/locking system. The tow motor has a corresponding gripping area

5 making attachment easy for the user and providing a positive grip location. The design of  
this system permits the tow motor to rotate inside the quick connect disconnect yoke once it  
is secured in place this enhances the ergonomics of the device accommodating height of the  
person as well as the terrain that the device may be used on such as up or down hills or  
curbs. It will be appreciated by those skilled in the art that a wide variety of magnetic,  
10 electromagnetic or mechanical clamping mechanisms could be utilized while staying within  
the board scope of this invention.

The chassis contains two axles that are supported by brackets internal to the tubular  
monocock chassis that also support the gearboxes and clutch mechanisms used to distribute  
15 power to the wheels when demanded by the electronics in response to the application of  
force by the user to the steering column.

In operation the motor control circuitry receives power from the battery module and  
distributes power to the motor drives in response to commands generated by a fixed or re-  
20 programmable electronic controller. The controller conditions and receives signals  
generated by two or more handle mounted switches that control the motors independently  
which vary the speed and direction of each motor thereby providing variation in forward  
and rearward direction and speed as well as steering by slowing or stopping one or the other  
motor. It will be appreciated by those skilled in the art that a wide variety of switch and  
25 sensor arrangements could be utilized as well. Another embodiment of this control  
incorporates displacement sensitive resistors mounted in the steering column and operating  
in accordance with the fixed or re-programmable algorithms stored in the electronics  
generates signals that determine the direction of rotation and amount of motive power (   
torque & speed) generated by each motor. This system responds to the operators  
30 movements adjusting speed according to the walking speed of the user as well as turning  
left or right moving forward or back. The system will enhance the man machine interface  
enhancing the ergonomics of the invention.

5 The steering column display and control unit is a separate detachable module that can be mounted on the various accessory load carrying platforms and containers to allow them to be pushed pulled and steered in response to the desires and actions of the user. The display comprises a small control panel that incorporates indicators and switches to control and display the mode of operation and to switch on and off the unit.

10

There has thus been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the invention that will be described hereinafter and which will form the subject  
15 matter of the claims appended hereto.

In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following  
20 description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. For example, while the use of two motors has been described, one or two or more motors could be utilized. Also, it is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting.

25

As such, those skilled in the art will appreciate that the conception, upon which this disclosure is based, may readily be utilized as a basis for the designing of other structures, methods and systems for carrying out the several purposes of the present invention. It is important, therefore, that the claims be regarded as including such equivalent constructions  
30 insofar as they do not depart from the spirit and scope of the present invention.


5

CLAIMS

**We Claim:**


- 10      1. A motorized towing device as described and shown.

FIG 1a




Base motor module unit without handle and control attached.

FIG 1b




¾ view of the base motor module with handle and controller attached

FIG 2



Side elevation of base motor module with handle and controller attached


**FIG 3**



**Front elevation of base motor module with handle and controller attached**




FIG 4




$\frac{3}{4}$  Assembly view

FIG 5




¾ view of handle and control and display, with force feedback steering and direction handle.

Fig 6 a




Tow motor shown with a wagon accessory, Wagon assembly has quick disconnect yoke system.

FIG 6 b




Tow motor shown with quick connect/disconnect clamping system on another typical accessory. Quick connect/disconnect system shown open ready to install on town motor.

Fig 6 c




Quick connect/disconnect system shown mounted on tow motor in the corresponding locating area with rotating yoke closing to "grip" the tow motor.

Fig. 6 d



Quick connect/disconnect shown closed, rotating yoke rotated into position and buckle type closure inserted into position for locking.

FIG 6 e



Quick connect/disconnect shown located into corresponding locating area with buckle in the "locked" position.